

Submittal Sheet

Submittal Sheet #0309044

Thin Wafer Head Drivall® Screws (252)

Product:	Item#	Description	Unit Pack
	10158W4	10 x 1-5/8-in, Thin Wafer Head, #4 Drill Point, Phillips, Clear Zinc, Bulk, (No Wings)	4,000
	101716	10 x 1-7/16-in, Thin Wafer Head, Drill Point, Phillips, Clear Zinc, Bulk (No Wings)	4,000
	101716W3RG	10 x 1-7/16-in, Thin Wafer Head, Drill Point, Phillips, GrabberGard, Bulk, Winged	4,000
	101716W3	10 x 1-7/16-in, Thin Wafer Head, Drill Point, Phillips, Clear Zinc, Bulk, Winged	4,000

Screw Series	Designation	Head Type	Nominal Diameter	Nominal Head Diameter	Nominal Gauge- TPI	Nominal Length	Point (No#)	Thread Length	Drilling Capacity Min#	Drilling Capacity Max#	Coating
Drivall	Heavy Gauge Steel	Wafer Head	0.19	0.453	#10-24	1.4375	Pilot #3	1.375	20 ga.	14 ga.	Z
Drivall	Heavy Gauge Steel	Wafer Head	0.19	0.453	#10-24	1.4375	Winged #3	1.375	20 ga.	14 ga.	Z, RG
Drivall	Heavy Gauge Steel	Wafer Head	0.19	0.453	#10-24	1.625	Pilot #4	1.15	20 ga.	14 ga.	Z

NOTE: RG = GrabberGard® Exterior Grade Coating

Application: GRABBER's Flat and Wafer Head Drivall® pilot point screw is used for the attaching 3/8 plywood to steel studs or track or metal door jambs, 14-20 gauge steel, and other sheathing to metal applications.

Description: Flat head, #2 Phillips recess drive, fine thread (24 TPI), clear zinc finish with extra sharp pilot drill point or winged pilot drill point. Drill point for heavy gauge steel (14-20g).

Directions: Use standard screw gun with depth sensitive nose piece. Suggested screw gun for optimum performance is 4 amps minimum and 0 to 2,500 rpm. Flat head is completely seated when the head is flush with the work surface. Overdriving may result in failure of the fastener or stripping of the head recess.

Certifications: All GRABBER® screw products are manufactured in facilities that are ISO 9001 certified. The fasteners comply with ASTM C1513 and C954.



SUBMITTAL APPROVALS:

JOB NAME

CONTRACTOR

DATE

TRADEMARKS:

The following trademark used herein is owned by Grabber Construction Products, Inc.: GRABBER.

NOTICE:

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.

Thin Wafer Head Drivall® Screws (252)



PRODUCT SPECIFICATIONS

Fastener Classification	Heavy Gauge Metal (18 or thicker)
Fastener Head	Thin Wafer
Fastener Drive	#2 Phillips, #3 Phillips
Fastener Gauge	#10
Fastener Point	#3 or #4 Drill, #3 Wing Drill
Fastener Package Type	Packaged Screws
Fastener Package Weight	1lb Box, 5lb Box, Bulk Box
Fastener TPI	24
Fastener Coating	Clear Zinc, GrabberGard, GrabberGard Gray

STANDARD CORROSION TEST RESULTS

Finish	Test	Standard/Protocol	Results
Gray Phosphate	Salt Spray Results	ASTM B117	24 hours, no red rust
Yellow Zinc	Salt Spray Results	ASTM B117	48 hours, no red rust
Clear Zinc	Salt Spray Results	ASTM B117	24 hours, no red rust
Dracrotized	Salt Spray Results	ASTM B117	500 hours, no red rust
GrabberGard	Salt Spray Results	ASTM B117	1,000 hours, no red rust
GrabberGard	Kesternich Results	DIN 50018, 2.0L	15 cycles, no red rust
304 Stainless Steel	Salt Spray Results	ASTM B117	1000 hours, no red rust
316 Stainless Steel	Salt Spray Results	ASTM B117	1500 hours, no red rust

Grabber's approved mill keeps tight control over all production standards and processes. Grabber's mill is ISO 9001 and ISO 14001 certified compliant ensuring Grabber fasteners meet or exceed the highest industry standards.