

Submittal Sheet

Submittal Sheet #0309042A

Bugle Head Drivall® Screws (240)

Product:	Item#	Description	Unit Pack
	B10350SDL2Z	10 x 3-1/2-in, Bugle Head, Drivall®, LOX®, 16TPI, Clear Zinc, Bulk	1,000
	14RG	6 x 1-1/4-in, Bugle Head, Drill Point, Phillips, GrabberGard Gray, Bulk	8,000
	C14Z	6 x 1-1/4-in, Bugle Head, Drivall®, Clear Zinc, Collated	1,000
	C14RG	6 x 1-1/4-in, Bugle Head, Drivall®, GrabberGard®, Collated	1,000
	14A	6 x 1-1/4-in, Bugle Head, Drivall®, Phosphate, Bulk	8,000
	C14S	6 x 1-1/4", Black - Collated	1,000
	C16RG	7 x 1-7/8-in, Bugle Head, Drivall®, GrabberGard®, Collated	1,000
	30MA	8 x 2-5/8-in, Bugle Head, Drivall®, Phosphate, Bulk	2,000
	16A	6 x 1-7/8-in, Bugle Head, Drivall®, Phosphate, Bulk	4,000
	B10400SDRG	10 x 4-in, Bugle Head, Drivall®, GrabberGard®, Bulk	1,000
	B10400SDL2Z	10 x 4-in, Bugle Head, Drivall®, LOX®, 16TPI, Clear Zinc, Bulk	1,000
	B10500SDRG	10 x 5-in, Bugle Head, Drivall®, GrabberGard®, Bulk	1,000
	B10500SDL2Z	10 x 5-in, Bugle Head, Drivall®, LOX®, 16TPI, Clear Zinc, Bulk	1,000
	15RG	6 x 1-5/8-in, Bugle Head, Drivall®, Phillips, GrabberGard Gray, Bulk	5,000
	16RG	6 x 1-7/8-in, Bugle Head, Drivall®, GrabberGard®, Bulk	4,000
	30SRG	8 x 2-3/8-in, Bugle Head, Drivall®, Phillips, GrabberGard Gray, Bulk	3,000
	30MRG	8 x 2-5/8-in, Bugle Head, Drivall®, Phillips, GrabberGard Gray, Bulk	2,000
	30LRG	8 x 3-in, Bugle Head, Drivall®, Phillips, GrabberGard Gray, Bulk	2,000
	C15Z	6 x 1-5/8-in, Bugle Head, Drivall®, Clear Zinc, Collated	1,000
	C16Z	7 x 1-7/8-in, Bugle Head, Drivall®, Clear Zinc, Collated	1,000
	C14RG8F	8 x 1-1/4-in, Bugle Head, Drivall®, Full Thread, GrabberGard®, Collated	1,000
	C15GG8P	8 x 1-5/8-in, Bugle Head, Pilot Point, Drivall®, GrabberGard®, Collated	1,000

Screw Series	Designation	Head Type	Nominal Diameter	Nominal Head Diameter	Nominal Gauge- TPI	Nominal Length	Point (No#)	Thread Length	Drilling Capacity Min#	Drilling Capacity Max#	Coating
Drivall	Heavy Gauge Steel	Bugle Head	0.138	0.321	#6-20	1.25	Drill #3	1	20 ga.	8 ga.	RG
Drivall	Heavy Gauge Steel	Bugle Head	0.138	0.321	#6-20	1.625	Drill #3	1.375	20 ga.	8 ga.	RG
Drivall	Heavy Gauge Steel	Bugle Head	0.138	0.321	#6-20	1.875	Drill #3	1.625	20 ga.	8 ga.	RG
Drivall	Heavy Gauge Steel	Bugle Head	0.164	0.321	#8-18	2.375	Drill #3	1.625	20 ga.	8 ga.	RG
Drivall	Heavy Gauge Steel	Bugle Head	0.164	0.321	#8-18	1.25	Drill #3	1	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Bugle Head	0.164	0.321	#8-18	2.625	Drill #3	1.625	20 ga.	8 ga.	RG
Drivall	Heavy Gauge Steel	Bugle Head	0.164	0.321	#8-18	3	Drill #3	1.875	20 ga.	8 ga.	RG
Drivall	Heavy Gauge Steel	Bugle Head	0.164	0.321	#8-18	3.5	Drill #3	2	20 ga.	8 ga.	RG
Drivall	Heavy Gauge Steel	Bugle Head	0.19	0.343	#10-16	3.5	Drill #3	2	20 ga.	8 ga.	Z, RG
Drivall	Heavy Gauge Steel	Bugle Head	0.19	0.343	#10-16	4	Drill #3	2	20 ga.	8 ga.	Z, RG
Drivall	Heavy Gauge Steel	Bugle Head	0.19	0.343	#10-16	4.5	Drill #3	2	20 ga.	8 ga.	YZ
Drivall	Heavy Gauge Steel	Bugle Head	0.19	0.343	#10-16	5	Drill #3	2	20 ga.	8 ga.	Z, RG

NOTE: Grabber screws with the item numbers ending in "A" are manufactured in the United States of America. Grabber American Made Screws are SPECIAL ORDER INVENTORY. CONTACT GRABBER FOR CURRENT PRICE AND AVAILABILITY. Grabber American Made Screws are SPECIAL ORDER INVENTORY. CONTACT GRABBER FOR CURRENT PRICE AND AVAILABILITY.

- YZ = Yellow Zinc
- CZ = Clear Zinc
- RG = GrabberGard
- A = USA Made

Application: The GRABBER Bugle Head Drivall Screw is designed specifically for the attaching 1/2" and 5/8" drywall to medium (18-14) gauge steel stud. This screw features a Bugle head design to eliminate drywall paper burrs, providing a smooth, clean, professional surface. Other applications include wood and core board to metal stud.


Description: Bugle Head, #2 Phillips recess, fine TPI, Grey Phosphate or Clear Zinc or GrabberGard Grey, with #3 drill point, compliant with ASTM C954.

Directions: Use standard screw gun with depth sensitive nose piece. Suggested screw gun for optimum performance is 4 amps minimum and 0 to 2,500 rpm. Bugle Head is completely seated when the head is flush with the work surface. Overdriving may result in failure of the fastener, the metal the fastener is attaching to or stripping of the head recess. Penetration of three thread pitches beyond the penetrated metal is the minimum.

Certifications: All GRABBER® screw products are manufactured in facilities that are ISO 9001 certified. The fasteners comply with the performance requirements of ASTM C954. ©2012 GRABBER Construction Products, Inc. GRABBER®, STREAKER®, DRIVALL®, LOX®, GRABBERGARD® and SCAVENGER® are registered trademarks of Grabber Construction Products, Inc.



Bugle Head Drill Point



SUBMITTAL APPROVALS:

JOB NAME

CONTRACTOR

DATE

TRADEMARKS:

The following trademark used herein is owned by Grabber Construction Products, Inc.: GRABBER.

NOTICE:

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.

Bugle Head Drivall® Screws (240)



PRODUCT SPECIFICATIONS

Fastener Classification	Heavy Gauge Metal (18 or thicker)
Fastener Head	Scavenger, Bugle
Fastener Drive	#2 Phillips, LOX #2
Fastener Gauge	#6, #7, #8, #10
Fastener Point	Drill, Drill, S-12, Pilot, #3 Drill
Fastener Package Type	Packaged Screws, Collated Screws (for automated feed systems)
Fastener Package Weight	5lb Box, Bulk Box
Fastener TPI	2, 14, 15, 16, 18, 19, 20
Fastener Coating	Black/Gray Phosphate, Clear Zinc, GrabberGard, GrabberGard Gray

STANDARD CORROSION TEST RESULTS

Finish	Test	Standard/Protocol	Results
Gray Phosphate	Salt Spray Results	ASTM B117	24 hours, no red rust
Yellow Zinc	Salt Spray Results	ASTM B117	48 hours, no red rust
Clear Zinc	Salt Spray Results	ASTM B117	24 hours, no red rust
Dracrotized	Salt Spray Results	ASTM B117	500 hours, no red rust
GrabberGard	Salt Spray Results	ASTM B117	1,000 hours, no red rust
GrabberGard	Kesternich Results	DIN 50018, 2.0L	15 cycles, no red rust
304 Stainless Steel	Salt Spray Results	ASTM B117	1000 hours, no red rust
316 Stainless Steel	Salt Spray Results	ASTM B117	1500 hours, no red rust

Grabber's approved mill keeps tight control over all production standards and processes. Grabber's mill is ISO 9001, ISO 14001 and ICC-ES certified compliant ensuring Grabber fasteners meet or exceed the highest industry standards.