

## Submittal Sheet

Submittal Sheet #0020032

### Grabber Cement Board Sharp Point Screws (228)

Product:	Item#	Description	Unit Pack
	CGHS8114LG	8 x 1-1/4-in, Flat Wafer Head, High Density BD Fine Thread, LOX 2, GrabberGard®, Collated	1,000
	GCB8125HL	8 x 1-1/4-in, Wafer Head, Alternating Thread, Phillips, GrabberGard Gray, Bulk	5,000
	GCB10350HL	10 x 3-1/2-in, Wafer Head, Alternating Thread, Phillips, GrabberGard Gray, Bulk	1,000
	GCB8158HL	8 x 1-5/8-in, Wafer Head, Alternating Thread, Phillips, GrabberGard Gray, Bulk	4,000
	GCB8238HL	8 x 2-3/8-in, Wafer Head, Alternating Thread, Phillips, GrabberGard Gray, Bulk	3,000
	CGHS8158LG	8 x 1-5/8-in, Flat Wafer Head, High Density BD Fine Thread, LOX 2, GrabberGard®, Collated	1,000
	CHSS8158JBW	Sharp Point Cement-board, 8 x 1-5/8" - Collated	1,000
	CGHS8238LG	8 x 2-3/8-in, Flat Wafer Head, High Density BD Fine Thread, LOX 2, GrabberGard®, Collated	1,000

Screw Series	Designation	Head Type	Nominal Diameter	Nominal Head Diameter	Nominal Gauge- TPI	Nominal Length	Point (No#)	Thread Length	Drilling Capacity Min#	Drilling Capacity Max#	Coating
Grabber	Cement Board	Wafer Head Ribbed	0.164	0.404	#8-15	1.25	Grabber	1.25	20 ga.	25 ga.	RG
Grabber	Cement Board	Wafer Head Ribbed	0.164	0.404	#8-15	1.625	Grabber	1.625	20 ga.	25 ga.	RG
Grabber	Cement Board	Wafer Head Ribbed	0.164	0.404	#8-15	2.25	Grabber	2.25	20 ga.	25 ga.	RG

**Application:** Attaches cement board to light gauge metal (25-20 ga.) or wood. Features a .40 diameter head and GrabberGard® exterior coating.

- Three lengths available 8 x 1-1/4-in, 8 x 1-5/8-in and 8 x 2-3/8-in
- 1000 hr corrosion resistant finish per ASTM B117
- .40-in Wafer head and countersinking nibs.
- Alternating High/Low threads for application in wood or metal.

**Description:** GRABBER cement board and high density sheathing screws have been specifically designed for use with cement board and high density exterior sheathing. These exterior grade corrosion resistant fasteners have a .40" (10.5mm) wafer head with nibs to facilitate seating and minimize strip out.

**Directions:** Use a standard screwgun with a depth sensitive nose piece. Suggested screwgun specification for optimal performance – 4 amps minimum and 2500 RPM. Install with head flush with board, no need to counter sink. Overdriving may result in failure of the fastener or strip-out of the work surface.

**Certifications:** All GRABBER® screw products are manufactured in facilities that are ISO 9002 and ISO 14001 certified and approved. The fasteners comply with ASTM C1513, as referenced in ICC ESR report ESR-1271, are approved for use in structures governed by the International Building Code 2006, 2009, 2012, International Residential Building Code 2006, 2009, and 2012.

SUBMITTAL APPROVALS:

.....  
JOB NAME

CONTRACTOR

DATE

**TRADEMARKS:**

The following trademark used herein is owned by Grabber Construction Products, Inc.: GRABBER.

**NOTICE:**

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.

## Grabber Cement Board Sharp Point Screws (228)



### PRODUCT SPECIFICATIONS

<b>Fastener Classification</b>	Exterior Wood, Cement Board
<b>Fastener Head</b>	Thin Wafer, Flat
<b>Fastener Drive</b>	#2 Phillips, LOX #2
<b>Fastener Gauge</b>	#8, #10
<b>Fastener Point</b>	Self Piercing Point, Sharp
<b>Fastener Package Type</b>	Packaged Screws, Collated Screws (for automated feed systems)
<b>Fastener Package Weight</b>	Mini Pack, 1lb Box, 5lb Box, Bulk Box
<b>Fastener TPI</b>	15
<b>Fastener Coating</b>	GrabberGard, GrabberGard Gray

### STANDARD CORROSION TEST RESULTS

Finish	Test	Standard/Protocol	Results
Gray Phosphate	Salt Spray Results	ASTM B117	24 hours, no red rust
Yellow Zinc	Salt Spray Results	ASTM B117	48 hours, no red rust
Clear Zinc	Salt Spray Results	ASTM B117	24 hours, no red rust
Dracrotized	Salt Spray Results	ASTM B117	500 hours, no red rust
GrabberGard	Salt Spray Results	ASTM B117	1,000 hours, no red rust
GrabberGard	Kesternich Results	DIN 50018, 2.0L	15 cycles, no red rust
304 Stainless Steel	Salt Spray Results	ASTM B117	1000 hours, no red rust
316 Stainless Steel	Salt Spray Results	ASTM B117	1500 hours, no red rust

Grabber's approved mill keeps tight control over all production standards and processes. Grabber's mill is ISO 9001, ISO 14001 and ICC-ES certified compliant ensuring Grabber fasteners meet or exceed the highest industry standards.